



PRAMAC LIFTER MANUAL STACKER MX516

Reference: HB305000000

MX series is not only an excellent compromise between price and performance but is also a very resistant machine. Reinforced forks, a pulley made of steel and forks driven by 4 rollers to the position set are some of the main features of the high quality of this stacker. The machine is also equipped with a foot pedal for the lifting of forks, which considerably reduces the operator's effort.

Foot brake

The foot brake, which is available on the MX and TX machines, performs the parking brake function.

Tiller

- The plastic cover increases the ergonomic character of the handle thus rendering the raising and transport operations even "lighter".
- The 3-position control lever (down, neutral, up) is positioned on the steering wheel to foster manoeuvrability.

The images are purely indicative.

Technical Sheet

Drive	Manual
Operator type	Pedestrian
Load capacity (Kg)	500
Load centre distance (mm)	600
Load axle to end forks (mm)	800
Wheel base (mm)	1240
Service weight (Kg)	200
Axle load, laden rear (Kg)	487
Axle load, laden front (Kg)	213
Axle load, unladen front (Kg)	123
Axle load, unladen rear (Kg)	77
Tyres: stabilizers wheels	NYLON
Tyres: rear wheels	NYLON

Diameter load rollers (mm)	80
Width load rollers (mm)	70
Diameter stabilizers wheels front (mm)	150
Width stabilizers wheels front (mm)	40
Quantity rear wheels	2
Tread front (mm)	600
Tread rear (mm)	380
Height mast lowered (mm)	2080
Normal free lifting (mm)	1510
Lift height (mm)	1510
Height mast extended (mm)	2080
Height of tiller in drive position max (mm)	1090
Height lowered (mm)	90
Overall length (mm)	1690
Length to face of forks (mm)	540
Overall width (mm)	740
Thickness fork (mm)	60
Width fork (mm)	170
Length fork (mm)	1150
Fork carriage width (mm)	550
Distance between fork arms (mm)	550
Ground clearance at centre of wheelbase (mm)	30
Aisle width (mm)	2166
Turning radius (mm)	1400
Lifting speed laden (m/s)	73
Lifting speed unladen (m/s)	73
Lowering speed laden (m/s)	0.16
Lowering speed unladen (m/s)	0.05
Type of lifting	Electric