



PRAMAC LIFTER ELECTRIC PALLET TRUCK CX12 800x520

Reference: CX12 800x520

PRAMAC LIFTER ELECTRIC TRANSPALLET CX12 800x520

PRAMAC Lifter CX12 800x520 cm CX series pallet truck is available in various versions equipped with MOSFET technology. The PRAMAC Lifter CX12 800x520 cm pallet truck is suitable for transporting loads on smooth or paved surfaces.

The small size and small turning radius make the PRAMAC Lifter CX12 pallet truck the ideal tools for working in small spaces such as trucks or small storage aisles. The PRAMAC Lifter CX12 pallet truck for sale in our catalog is Made in Italy.

The PRAMAC Lifter CX12 pallet truck is built with 800x520 cm forks and two rear wheels and one front drive wheel. This pallet truck has a load capacity of 1200 kg with a lifting height of 115 mm. The storage aisle is 1382 mm while the turning radius is 918 mm.

The Pramac Lifter CX12 electric pallet truck is designed to simplify and optimize load handling operations within warehouses, industrial plants and other work environments. With a load capacity of 1200 kg and a size of 800x520 mm, it offers a reliable solution for transporting materials efficiently.

With a B1 width, equal to the fork gauge, and an L2 size of 360 mm, the CX12 electronic pallet truck proves to be the ideal tool for pallet handling on trucks, in supermarket aisles and in any application where space is limited. In its category, such a machine is therefore the best configuration in terms of chassis width, operating weight and turning radius, ensuring great maneuverability and compactness.

Technical characteristics PRAMAC Lifter CX12 800x520 cm:

Propulsion type: Electric
Drive system: Accompaniment
Load capacity: 1200 kg
Quantity of rear wheels: 2
Quantity of front wheels: 1 drive
Lifting height: 115 mm
Total length: 1160 mm
Total width: 520 mm
Width of forks: 150 mm
Forks length: 800 mm
Width between forks: 520 mm
Stowage aisle: 1382 mm
Turning radius: 918 mm
Travel speed with load: 4.3 km/h
Travel speed without load: 4.8 Km/h
Traction motor power: 0.35 KW

The trolley is sold including batteries and charger.

If you are looking for another kind of product for [transporting and storing goods](#) then you can browse selection of products.

Images and technical data are not binding.

Technical Sheet

Drive	Electric
Operator type	Pedestrian
Load capacity (Kg)	1200
Load centre distance (mm)	400
Load axle to end forks (mm)	536
Wheel base (mm)	769
Service weight (Kg)	150
Axle load, laden rear (Kg)	1017
Axle load, laden front (Kg)	333
Axle load, unladen front (Kg)	121
Axle load, unladen rear (Kg)	29
Tyres: front wheels	RUBBER
Tyres: stabilizers wheels	POLY.I.
Tyres: rear wheels	NYLON
Diameter steering wheels (mm)	186
Width steering wheels (mm)	50
Diameter load rollers (mm)	82
Width load rollers (mm)	82
Diameter stabilizers wheels front (mm)	75
Width stabilizers wheels front (mm)	32
Quantity rear wheels	2
Quantity front wheels	1 driven
Tread front (mm)	369
Tread rear (mm)	371
Lift height (mm)	115
Height of tiller in drive position max (mm)	1345
Height of tiller in drive position min (mm)	885
Height lowered (mm)	85
Overall lenght (mm)	1160
Lenght to face of forks (mm)	360

Overall width (mm)	520
Thickness fork (mm)	55
Width fork (mm)	150
Lenght fork (mm)	800
Distance between fork arms (mm)	520
Ground clearance at centre of wheelbase (mm)	30
Aisle width (mm)	1382
Turning radius (mm)	918
Travel speed laden (Km/h)	4.3
Travel speed unladen (Km/h)	4.8
Lifting speed laden (m/s)	0.03
Lifting speed unladen (m/s)	0.04
Lowering speed laden (m/s)	0.05
Lowering speed unladen (m/s)	0.02
Max gradeability laden (%)	10
Max gradeability unladen (%)	25
Service brake	Electric
Drive motor power (KW)	0.35
Lift motor power (KW)	0.4
Battery voltage (V)	24
Battery capacity min (Ah)	60
Battery capacity max (Ah)	60
Battery weight min (Kg)	25
Battery weight max (Kg)	40
Energy consumption according to VDI cycle (KWh/h)	0.28
Sound level at driver's ear	67