



ELC LUMAPHORE LED 200L

Reference: LUMLED0200001P

LUMAPHORE® 200L complements perfectly the existing LUMAPHORE® LED range. Almost as powerful as the LUMAPHORE® CFL 440, it is lighter, smaller and more durable product. It is fitted with a carrying handle as standard and can be suspended anywhere. LUMAPHORE® 200L offers powerful illumination of 16000 Lumens with 170 Watts.

It is the ideal solution for many industry sectors:

- Civil engineering
- Rail works
- Road safety departments
- Road surfacing companies
- Water and utilities companies
- Council services

Benefits of the LUMAPHORE® LED 200L:

- 900 m² area of lighting with 170 W output
- 100% immediate Lighting
- Lightweight
- Carrying handle
- Resistant to adverse weather conditions

The images are purely indicative.

Technical Sheet

Protection degree	IP44
Diameter (Ø)	22.5
Maximum height (m)	3
Number of LED modules	10
Number of LEDs per module	42
Total lighting output (W)	160
Power of electricity supply (W)	170
Connecting cable 3x1.5 mm ² (m)	10
Average life of LEDs (hrs)	50000
Immediate illumination	Yes

Guyed tower	Si
Temperature range for use (°C)	-15 / +40
Colour temperature (°K)	4700
Lumens / module / COB (Lm)	1600
Color rendering index	Greater than 82
Average assembly time (min)	2
Illuminated area (m ²)	900
Total lumens (Lm)	16000
Length (mm)	620
Weight (Kg)	4.7