



BM2 HOT AIR GENERATOR GP 105M

Reference: 03GP157GP105M

BM2 HOT AIR GENERATOR GP 105M

BM2 GP105M is an manual start LPG-fuelled hot air generator, perfect for heating closed but ventilated rooms such as construction sites, greenhouses and farms.

BM2 GP105M is powered by high-pressure LPG, with an integrated, direct-burning burner. BM2 GP105M hot air generator is made equipped with manual ignition by piezoelectric. For their supply they are usually connected to LPG cylinders, which makes them handy and very economical.

The BM2 GP105M hot air generator comes complete with:

- Built-in LPG burner
- Safety thermostat
- Control with thermocouple and gas valve
- Electric power cord with plug
- Manual ignition with piezo-electric system
- Complies with UNI EN 1596:2008

TECHNICAL FEATURES BM2 GP105M

Maximum heat output: 108.71 KW / 93590 kcal/h / 371390 BTU/h

Minimum heat output: 48.81 KW / 41970 kcal/h / 166545 BTU/h

Power supply: LPG

Maximum gas consumption: 6.899 Kg/h

Minimum gas consumption: 3.094 Kg/h

Gas pressure: 1.5 - 0.4 bar

Efficiency: 100 %

Air flow rate: 3700 m³/h

Air temperature at 20°C: 71 °C

Electrical power: 400 W

Voltage: 230 V

Phase: Single phase

Frequency: 50 Hz

Width: 835 mm

Length: 438 mm

Height: 606 mm

Dry weight: 26 Kg

Are you looking for a hot air generator with different technical characteristics? [Here](#) you can find the full range of BM2 hot air generators or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase
Fuel	LPG
Frequency (Hz)	50
Voltage (V)	230
Max rated heat power	108.71 KW - 93590 Kcal/h - 371390 BTU/h
Min rated heat power	48.81 KW - 41970 Kcal/h - 166545 BTU/h
Max Gas consumption (Kg/h)	6.899
Min Gas consumption (Kg/h)	3.094
Gas pressure (bar)	1.5±0.4
Heat efficiency (%)	100
Air flow (m ³ /h)	3700
Air temperature at 20°C (°C)	71
Power consumption (W)	400
Length (mm)	835
Width (mm)	438
Height (mm)	606
Dry weight (Kg)	26