



JANUS CBF02403M Switching Battery Charger 28V - 3A

Reference: CBF02403M

CBF02403M Switching Battery Charger 28V - 3A

The Battery Charger CBF02403M is able to charge lead industrial acid batteries efficiently and safely thanks to its sophisticated protections

The industrial battery charger CBF02403M is born out of a need for a reliable charger that can be installed and forgotten.

The robust metal housing is equipped with fixing eyelets for various needs. The connections are made through removable terminal blocks.

All models have a Led which indicates the operating condition.

Battery chargers CBF02403M have an optocoupled signalling output and a RS485 Modbus communication port for connection to external systems.

TECHNICAL FEATURES CBF02403M

Voltage: 230 V

Frequency: 50 / 60 Hz

Output voltage: 24 V

Rated current: 3 A

Protection class: Reverse, short circuit, high temperature

Battery Type: Lead Acid

Length: 154 mm

Width: 95 mm

Height: 50 mm

Looking for an industrial battery charger with different technical features? [Here](#) you can find our section dedicated to industrial battery chargers

Images and technical data are not binding.

| | |
|----------------------------|---|
| Frequency (Hz) | 50 / 60 |
| Voltage (V) | 230 |
| Cooling | Natural convection |
| Protection degree | Reverse polarity, short circuit, high temperature |
| Output voltage (V) | 24 |
| Nominal current (A) | 3 |
| Battery type | Lead acid |
| Operating temperature (°C) | -40 / +50 |
| Length (mm) | 154 |
| Width (mm) | 95 |
| Height (mm) | 50 |
| Overload protectors | Yes |