

## SINCRO E3 2-24/120 Synchronous DC Alternator 2.9 KW AVR



Reference: E3 2-24/120

Designed for applications requiring 24 & 48 VDC low voltage supply, Sincro DC power solutions are suitable both as battery chargers and emergency power supplies of auxiliary circuits, in the telecommunication, transports and industrial field.

### Applications

- Battery chargers
- Low voltage LED light towers
- Power supply of auxiliary circuits, high/medium voltage disconnectors coils, signalling devices
- Power supply of monitoring and alarm systems

### General features

- AVR electronic voltage regulation
- Based on three-phase synchronous alternators
- 1500 rpm or 3000 rpm with large speed tolerance
- Constant DC output voltage
- Adjustable output voltage
- Current overload protection
- Fan cooled
- Complying with EN 60034-1, IEC 60034-1, ISO 8528-3

### Sectors of use

- Telecommunications
- Industry
- Transports
- Military

### Advantages

- High voltage stability in a large speed range
- High efficiency
- Low voltage ripple
- High reliability
- Available with the most common couplings
- Fast recovery time during transient by step load variation

Not binding images and technical data.

## Technical Sheet

Frequency (Hz)

50

|                    |                |
|--------------------|----------------|
| Voltage (V)        | 24             |
| Engine rpm (rpm)   | 3000           |
| Poles              | 2              |
| Power (KW)         | 2.9            |
| Protection degree  | IP23           |
| Current (A)        | 120            |
| Brushes            | Yes            |
| Type of alternator | Constant Speed |
| Voltage regulator  | AVR            |
| Weight (Kg)        | 20.2           |