

YAMAHA EF 3000 ISE



Reference: EF3000ISE

Tutta la potenza che serve per ogni uso, dalle macchine per il caffè alle seghe circolari, in un'unità compatta e facile da usare. EF3000iSE offre una capacità di 3,0 kVA e un tempo di funzionamento massimo di oltre 20 ore a $\frac{1}{4}$ del carico nominale in modalità economizzatore. Nonostante la considerevole potenza, EF3000iSE ha una rumorosità di appena 51* dB (A). Le 4 ruote di cui è dotato, poi, rendono più facile che mai trasportarlo da un posto all'altro. Il controllo intelligente della valvola a farfalla è in grado di rilevare il carico e di regolare automaticamente di conseguenza la velocità del motore, migliorando l'efficienza del consumo di carburante e riducendo la rumorosità. A $\frac{1}{4}$ del carico nominale da 7 metri.

L'immagine è puramente indicativa

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3
Continuous power single phase (KW)	2.8
Maximum power single phase (KVA)	3
Continuous power single phase (KVA)	2.8
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230

Engine	Yamaha MZ175
Engine rpm (rpm)	4000
Starting system	Manual / Electric
Engine capacity (cm ³)	171
Oil capacity (L)	0.6
Fuel tank capacity (L)	13
Consumption (L/h)	1.63
Running time (h)	8
Acoustic power	88 dB(A)
Acoustic pressure	51 dB(A)
Length (mm)	680
Width (mm)	445
Height (mm)	555
Dry weight (Kg)	68
Inverter	Yes
AVR	No
Compound	No
Silenced	Yes
Super silenced	No