



LARIUS JOLLY K56501 AIRLESS PISTON TROLLEY PAINTER

Reference:

LARIUS JOLLY K56501 AIRLESS PISTON COATING PUMP

LARIUS JOLLY K56501 is an airless high-pressure airless paint pump (hence the term AIRLESS) capable of delivering a maximum flow of 1.8 l/m.

LARIUS JOLLY K56501 is an "electric piston pump" driven by an electric motor coupled to a gear reducer. An eccentric shaft and a connecting rod provide the reciprocating motion necessary for the operation of the piston of the "pumping unit". The movement of the piston creates a depression. The product is sucked in, pushed towards the pump outlet and sent through the high pressure hose to the gun.

An electronic device, placed on the side of the reduction box, allows to regulate and control the pressure of the material coming out of the LARIUS JOLLY K56501 pump. When the pressure reaches the set value, the motor stops and restarts when the value decreases.

A safety valve against overpressure guarantees the absolute reliability of the equipment. LARIUS JOLLY K56501 is equipped with a trolley complete with handle that allows a comfortable and easy transport.

For the correct functioning of the LARIUS JOLLY K56501 it is recommended to respect the "minimum necessary powers". The use of lower powers than those indicated may compromise the integrity and operation of the equipment.

LARIUS JOLLY K56501 is complete with line filter, 60 Mesh screen, 1/4" anti-pulsation hose M16x1.5 of 15 mt. AT250 airless gun with M16x1.5 swivel coupling, Super Fast Clean base, Super Fast Clean 17-40 nozzle.

TECHNICAL CHARACTERISTICS LARIUS JOLLY K56501

Single-phase power supply: 230Vac - 50Hz
Motor-generator power supply: minimum 4Kw asynchronous
Motor power 0.65 Kw
Max working pressure: 210 bar
Max flow rate: 1.8 L/min
Material outlet: M16 x 1.5
Max nozzle size: 0.019"
Sound pressure level ? 80dB(A)
Length: 580 mm
Width: 540 mm
Height: 995 mm
Weight: 16 Kg

Looking for an electric pump with different features? [Here](#) you can find the full range of LARIUS and other specialist brands

Images and technical data are not binding and may be subject to revision by the supplier

Technical Sheet

| | |
|----------------------------------|--------------|
| Phase | Single phase |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 |
| Net power (kW) | |
| Pressure (bars) | 220 |
| Length (mm) | 580 |
| Width (mm) | 540 |
| Height (mm) | 995 |
| Maximum paint flow rate (Lt/min) | 1.9 |
| Number paint colors | 1 |
| Feed Type | Single-Phase |
| Number of guns supported | 1 |
| Nozzle's largest diameter | 0.021" |
| Version | Trolley |
| Type of pumping group | Piston |
| Weight (Kg) | |