



CGM 10DET - APERTO CON CENTRALINA AUTOMATICA

Reference: CGM 10DET APERTO AUTOMATICO /

Technical Sheet

| | |
|------------------------------------|----------------------------|
| Phase | Single phase / Three phase |
| Maximum power three phase (KW) | 8.8 |
| Continuous power three phase (KW) | 8 |
| Maximum power three phase (KVA) | 11 |
| Continuous power three phase (KVA) | 10 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 / 400 |
| Engine | KOHLER 25LD 330/2 |
| Engine rpm (rpm) | 3000 |
| Starting system | Electric |
| Engine capacity (cm ³) | 654 |
| Number cylinders | 2 |
| Oil capacity (L) | 1.5 |
| Cooling | Air |
| Alternator | With brushes |
| Poles | 2 |
| Fuel tank capacity (L) | 4 |
| Consumption (L/h) | 2 at 75% of the load |
| Running time (h) | 2 al 75% del carico |
| Acoustic pressure | 77 dB(A) at 7 m |

| | |
|---------------------|--------------|
| Length (mm) | 900 |
| Width (mm) | 600 |
| Height (mm) | 700 |
| Dry weight (Kg) | 135 |
| Silenced | No |
| Super silenced | No |
| ATS Switch device | Optional ATS |
| Voltage regulator | Compound |
| Engine manufacturer | Kohler |
