



CGM 12.5DE - COFANATO CON CENTRALINA MANUALE

Reference: CGM 12.5DE COFANATO MANUALE /

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	11
Continuous power single phase (KW)	10
Maximum power single phase (KVA)	13.75
Continuous power single phase (KVA)	12.5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	N.1 x 230V 63A 3P CEE / N.1 x 230V 16A 3P CEE
Engine	KOHLER 25LD 425/2
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	851
Number cylinders	2
Oil capacity (L)	1.7
Cooling	Air
Alternator	Linz, brushless
Poles	2
Protection degree	IP55
Bore x stroke (mm)	75 x 77.6
Fuel tank capacity (L)	10

Consumption (L/h)	2.8 at 75% of the load
Running time (h)	3.6
Acoustic pressure	70 dB(A)
Length (mm)	1200
Width (mm)	690
Height (mm)	840
Dry weight (Kg)	235
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	Capacitor
Engine manufacturer	Kohler