



CGM 12.5DET - COFANATO CON CENTRALINA MANUALE

Reference: CGM 12.5DET COFANATO MANUALE /

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	11
Continuous power three phase (KW)	10
Maximum power three phase (KVA)	13.8
Continuous power three phase (KVA)	12.5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 32A 5P CEE - 1 x 230V 16A 3P CEE
Engine	KOHLER 25LD 330/2
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	851
Number cylinders	2
Oil capacity (L)	1.7
Cooling	Air
Alternator	With brushes
Poles	2
Protection degree	IP55
Fuel tank capacity (L)	10
Consumption (L/h)	2.8 at 75% of the load

Running time (h)	3.6
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	1200
Width (mm)	690
Height (mm)	840
Dry weight (Kg)	235
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	Compound
Engine manufacturer	Kohler