



## CGM 12.5DE - APERTO CON CENTRALINA AUTOMATICA

Reference: CGM 15DE COFANATO MANUALE /

### Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	13.2
Continuous power single phase (KW)	12
Maximum power single phase (KVA)	16.5
Continuous power single phase (KVA)	15
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	N.1 x 230V 63A 3P CEE / N.1 x 230V 16A 3P CEE
Engine	KOHLER 25LD 425/2
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	954
Number cylinders	2
Oil capacity (L)	2.5
Cooling	Air
Alternator	Linz, brushless
Poles	2
Protection degree	IP55
Fuel tank capacity (L)	50
Consumption (L/h)	3.2

Running time (h)	15.6
Acoustic pressure	73 dB(A) at 7 m
Length (mm)	1450
Width (mm)	800
Height (mm)	1150
Dry weight (Kg)	360
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	Capacitor
Engine manufacturer	Kohler