



## CGM 12.5DE - APERTO CON CENTRALINA AUTOMATICA

Reference: CGM 15DET COFANATO MANUALE /

### Technical Sheet

Maximum power three phase (KW)	13.2
Continuous power three phase (KW)	12
Maximum power three phase (KVA)	16.5
Continuous power three phase (KVA)	15
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 240
Sockets configuration	1 x 400V 32A 5P CEE - 1 x 230V 16A 3P CEE
Engine	KOHLER 25LD 425/2
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	954
Number cylinders	2
Oil capacity (L)	2.5
Cooling	Air
Alternator	With brushes
Poles	2
Protection degree	IP55
Fuel tank capacity (L)	50
Consumption (L/h)	3.2
Running time (h)	15.6

Acoustic pressure	73 dB(A) at 7 m
Length (mm)	1450
Width (mm)	800
Height (mm)	1150
Dry weight (Kg)	360
Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	Compound
Engine manufacturer	Kohler
Phase	Single phase / Three phase