



TELWIN TECHNOLOGY 238 CE/MPGE 230V ACX ALUMINIUM CARRY CASE

Reference: 816252

MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking.
Designed for welding cellulosic electrodes and coated electrodes such as aluminium, rutile, basic, stainless steel and cast iron electrodes with diameter up to 4 mm.

It can be connected to motorgenerators.

Features:

- Compact and light
- High welding current stability in spite of mains voltage fluctuations
- Regulation of arc force and hot start according to the type of electrode in use
- Anti-stick device
- Thermostatic, overvoltage, undervoltage, overcurrent protections.

Complete with MMA welding accessories and aluminium carry case.

Not binding images and technical data.

Technical Sheet

Phase	Single phase
Frequency (Hz)	50 / 60
Voltage (V)	230
Efficiency (%)	84
Protection degree	IP23
Maximum permissible current (A)	36
No-load voltage (V)	102
Regulation current (A)	5 - 180
Diameter electrodes (mm)	1.6 - 4
Type of welding current	DC
Type of welding	MMA / MIG
Current max (A)	180
Length (mm)	465
Width (mm)	185

Height (mm)	355
Voltage regulator	Inverter
Weight (Kg)	10.1
