



TELWIN SUPERIOR 320 CE VRD 230-400V

Reference: 816036

MMA and TIG-LIFT inverter welding machine in direct current (DC), with microprocessor control. Designed for welding cellulosic electrodes and coated electrodes such as aluminium, rutile, basic, stainless steel, cast iron with diameter up to 6 mm.

Features:

- Compact and light
- High welding current stability in spite of mains voltage fluctuations
- Immediate control of the welding droplets transfer
- Regulation of arc force and hot start according to the type of electrode in use
- Anti-stick device
- VRD device
- Remote control connector
- Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.

Not binding images and technical data.

Technical Sheet

Phase	Single phase / Three phase
Frequency (Hz)	50 / 60
Voltage (V)	230 / 400
Efficiency (%)	90
Protection degree	IP23
Maximum permissible current (A)	19 / 24.4
No-load voltage (V)	60 / 63
Regulation current (A)	10 - 250 / 10 - 270
Diameter electrodes (mm)	1.6 - 6
Type of welding current	DC
Type of welding	MMA / MIG
Current max (A)	220 / 270
Length (mm)	460

Width (mm)

Height (mm)

Voltage regulator

Inverter

Weight (Kg)

10.2
