



TELWIN MOTOINVERTER 204 CE HONDA

Reference: 815793

TELWIN MOTOINVERTER 204 CE MOTOR WELDING MACHINE 6,6KW

TELWIN MOTOINVERTER 204CE is a motor welder equipped with a Honda GX270 engine powered by gasoline, delivers a three-phase power of 6.6KW.

TELWIN MOTOINVERTER 204CE is a petrol engine driven welder with HONDA inverter technology engine with high frequency permanent magnet alternator for MMA and TIG-DC electrode welding with smear ignition.

TELWIN MOTOINVERTER 204CE allows incredible flexibility of use with a wide variety of electrodes: rutile, basic, cellulosic, stainless, cast iron, etc. It can also be used as a direct current (DC) generator for powering power tools such as drills, grinders, etc.

Features:

- 4-stroke gasoline engine with recoil start and air cooling
- Automatic block for no oil
- Motor overspeed protection
- Continuous adjustment of the welding current
- High stability of the current to variations in motor speed
- Arc force devices, hot start, anti-stick
- Welding-generator selector switch
- Thermostatic protection.

THE TECHNICAL CHARACTERISTICS TELWIN MOTOINVERTER 204CE

Phase Type: Single-Phase
Maximum Power: 6.6KW
Frequency: 50 Hz
Voltage: 230 V
Welding Current Type: DC
Welding Type: MMA / TIG
No-load Voltage: 112 V
Current Adjustment: 5-190 A
Maximum Current: 160 A
Electrode Diameter: 1.6 - 4 mm
Fuel: Gasoline

Motor: Honda GX270
Start: Manual
Length: 840 mm
Width: 470 mm
Height: 480 mm
Weight: 58 Kg

Are you looking for a welding machine with different technical characteristics? [Here](#) you can find the whole range TELWIN or other specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Engine	Honda GX270, 4 stroke
Engine rpm (rpm)	3400
Starting system	Manual
Engine capacity (cm ³)	270
Cooling	Air
Power (KW)	6.6
Protection degree	IP23
No-load voltage (V)	112
Regulation current (A)	5 - 190
Diameter electrodes (mm)	1.6 - 4
Type of welding current	DC
Type of welding	MMA / MIG
Current max (A)	160
Fuel tank capacity (L)	6
Acoustic power	97 dB(A)
Length (mm)	840
Width (mm)	470
Height (mm)	480
Voltage regulator	Inverter
Weight (Kg)	58