



TELWIN MOTOINVERTER 264DCE

Reference: 815980

TELWIN MOTOINVERTER 264DCE MOTORWELDING 8,1KW

TELWIN MOTOINVERTER 264DCE is a motorwelder equipped with a Lombardini 15LD440 engine powered by gasoline, provides a three-phase power of 8.1KW.

TELWIN MOTOINVERTER 264DCE is a petrol driven welder with inverter technology with high frequency permanent magnet alternator for MMA and TIG-DC electrode welding with smear ignition.

TELWIN MOTOINVERTER 264DCE with inverter technology and high-frequency permanent magnet alternator for MMA and TIG-DC electrode welding with spark ignition.

TELWIN MOTOINVERTER 264DCE has flexibility of use with a wide variety of electrodes: rutile, basic, cellulosic, stainless, cast iron, etc. It can also be used as a direct current (DC) generator to power power tools such as drills, grinders, etc.

Features:

- Automatic block for lack of oil
- Motor overspeed protection
- Continuous adjustment of welding current
- High stability of the current to the variations of the engine revolutions
- Hot start and anti-stick devices
- Arc force adjustment
- Welder-generator selector
- Thermostatic protection.

TECHNICAL FEATURES TELWIN MOTOINVERTER 264DCE

Phase Type: Single-Phase

Power: 8.1 KW

Mechanical Power: 11 Hp

Frequency: 50 Hz

Voltage: 230 V

Welding Current Type: DC

Welding Type: MMA / TIG

No-load Voltage: 113 V

Current Adjustment: 5-230 A

Maximum Current: 200 A

Electrode Diameter: 1.6 - 5 mm

Fuel: Diesel
 Engine: Lombardini 15LD440
 Boosting: Electric
 Length: 1050 mm
 Width: 580 mm
 Height: 720 mm
 Weight: 107 Kg

Are you looking for a welding machine with different technical characteristics? [Here](#) you can find the whole range of TELWIN or other specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Engine	Lombardini 15LD440
Engine rpm (rpm)	3500
Starting system	Electric
Engine capacity (cm ³)	442
Cooling	Air
Power (KW)	8.1
Protection degree	IP23
No-load voltage (V)	113
Regulation current (A)	5 - 230
Diameter electrodes (mm)	1.6 - 5
Type of welding current	DC
Type of welding	MMA / MIG
Current max (A)	200
Fuel tank capacity (L)	5
Acoustic power	98 dB(A)
Length (mm)	1050
Width (mm)	580
Height (mm)	720
Voltage regulator	Inverter
Weight (Kg)	107