



## TELWIN SUPERMIG 380 230-400V

Reference: 822043

MIG-MAG/FLUX/BRAZING welding machine with 4 rolls, separate wire feeder, fit for use in the industrial field.  
 Flexibility of use with a wide range of materials such as steel, stainless steel, high strength steels and aluminium.

Features:

- Very strong
- Numerous steps for regulation of arc voltage
- Regulation of spot welding time
- Two positions for reactance
- Thermostatic protection

Thanks to the extensions (optional) it is possible to increase the working range between wire feeder and power source up to 10 meters.

Complete with MIG-MAG welding accessories.

Not binding images and technical data.

### Technical Sheet

Phase	Single phase / Three phase
Frequency (Hz)	50 / 60
Voltage (V)	230 / 400
Protection degree	IP22
No-load voltage (V)	43
Adjustment positions	18
Regulation current (A)	40 - 350
Ø steel welding wire (mm)	0.6 - 1.6
Ø inox welding wire (mm)	0.8 - 1.6
Ø aluminium welding wire (mm)	0.8 - 1.2
Ø flux cored welding wire (mm)	1 - 1.6
Ø brazing wire (mm)	0.8 - 1.2
Type of welding	MIG-MAG
MIG-MAG welding	MIG-MAG/FLUX/BRAZING

---

Current max (A)	350
Length (mm)	890
Width (mm)	453
Height (mm)	1285
Weight (Kg)	101

---