



MARINE GENERATOR SET KOHLER 18 EFKOZD Single-phase 18 kVA

Reference: KOHLER 18 EFKOZD 230

Super-silenced single-phase KOHLER 18EFKOZD marine generator 18 KVA AVR

Generator Kohler 18EFKOZD singlephase 18 KVA with 1500 rpm motor. The KOHLER 18EFKOZD singlephase generator is built with a soundproof enclosure that makes it **supersilenced**. The KOHLER 18EFKOZD singlephase generator is built with a 4-cylinder, 4-cycle Kohler diesel-powered engine, closed cooling system with heat exchanger. The single-phase KOHLER 18EFKOZD generator alternator is brushless, with **AVR** voltage regulator and water-cooled. The AVR voltage regulator protects your connected sensitive devices from power surges. With its small size, the nautical generator 18EFKOZD is also suitable on boats of various sizes.

Technical features:

Phase type: Single phase
Single phase continuous power at 230 V: 18 KW
Single phase continuous power at 240 V: 14. 5 KW
Fuel: Diesel
Frequency: 50 Hz
Voltage: 230 V or 240 V
Motor: Kohler
Motor speed: 1500 rpm
Length: 1197 mm
Width: 652.5 mm
Height: 711 mm
Dry weight: 462 kg

Features of the KOHLER 18EFKOZD generator

- Class H insulation
- Multi-voltage adjustability
- Voltage adjustment of 1.0%.
- Radio suppression

Engine features of the KOHLER 18EFKOZD generator

- Diesel
- Environmental Protection Agency (EPA) certified for compliance with Tier III marine auxiliary standards (60 Hz model only)
- Four cylinders
- Four cycles
- Closed cooling system
- Heat exchanger
- Electric fuel lift pump

- Lifting eyelet
- Low oil pressure shutdown
- High temperature engine shutdown
- Low seawater pressure shutdown
- Vibromount
- Belt guard
- Disposable oil filter
- Oil drain valve
- Disposable fuel filter

Features of the KOHLER 18EFKOZD generator alternator

- Brushless rotating field design allows power to be obtained from stationary conductors.
- Windings are vacuum-impregnated with epoxy paint for reliability and long life.
- Rotors are dynamically balanced to minimize vibration.
- Copper windings ensure minimal heat buildup. Insulation meets NEMA standards for Class H insulation.
- Connected directly to the motor, the generator features sealed precision ball bearings with a precision machined steel sleeve in the end bracket to prevent shaft misalignment and extend bearing life.
- Mounted on a drip-proof tray.
- Equipped with a four-conductor reconnectable stator.
- Capable of withstanding a line-to-neutral short-circuit current of up to 300% of rated current for up to 2 seconds. (Short circuit performance IEC 60092-301).

Other marine generators such as the KOHLER 18EFKOZD can be found by browsing the entire catalog of [marine generators](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Continuous power single phase (KW)	18
Continuous power single phase (KVA)	18
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Engine	Kohler
Engine rpm (rpm)	1500
Speed governor	Mechanical
Engine capacity (cm ³)	2500
Number cylinders	4
Cooling	Water
Bore x stroke (mm)	88 x 102
Compression ratio	17 : 1
Motor insulation class	H
Consumption (L/h)	3.8 at 75% of the load / 5 at 100% of the load
Length (mm)	1197

Width (mm)	652.5
Height (mm)	711
Dry weight (Kg)	462
Silenced	Yes
Super silenced	Yes
Type of combustion	Direct
Product type	Generator
Voltage regulator	AVR
Engine manufacturer	Kohler
