



GENERATOR FISCHER PANDA 60-4 PMS

Reference: FP0014985

MARINE GENERATOR FISCHER PANDA 60-4PMS SUPERSILENCED 58.8 KVA

Generator for boats Fischer Panda 60-4PMS three-phase 58.8 KVA with 1500 rpm motor. The Fischer Panda 60-4PMS three-phase marine generator is designed with a soundproof cabin that significantly reduces noise emissions and makes it super-silent. The Fischer Panda 60-4PMS three-phase generator is designed with a Deutz diesel-powered engine. The Fischer Panda 60-4PMS three-phase marine generator alternator is 4-pole with H insulation class. Thanks to its compactness, size and low weight, the Fischer Panda 60-4PMS three-phase marine generator is also perfect for installation on boats with tight spaces. So many advantages in only one product!

Specifications of the Fischer Panda 60-4PMS super-silent marine generator:

Phase Type: Three-phase
Maximum Output: 50 kW
Continuous Output: 45 kW
Maximum Output: 58.8 kVA
Continuous Output: 52.9 kVA
Frequency: 50 Hz
Voltage: 400 V
Engine rpm: 1500 rpm
Displacement: 4040 cc.
Cooling: Water
Sound Cover Type: MPL 6DS
Length: 1530 mm
Width: 920 mm
Height: 1000 mm
Dry weight: 1200 Kg

Based on the rugged Fischer Panda 60-4PMS generator set, these heavy duty (HD) versions operate at 1500 rpm / 50Hz. The Fischer Panda 60-4PMS generator is enclosed in a super quiet soundproofed capsule. The generators are heavier than standard PMS generators. They use a heavy-duty diesel engine and because they run at 1500 rpm, they have a 4-wire coil, which also means that the alternator has a heavier 4-pole construction. The heavy-duty construction and low rpm results in a durable and quiet generator set.

Discover other marine generators such as the Fischer Panda 60-4PMS but with different technical specifications by browsing through the entire catalogue of [marine generators](#).

Images and technical data are not binding.

...

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	50
Continuous power three phase (KW)	45
Maximum power three phase (KVA)	58.8
Continuous power three phase (KVA)	52.9
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	Deutz BF4M2012C
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm ³)	4040
Number cylinders	4
Cooling	Water
Poles	4
Motor insulation class	H
Length (mm)	1530
Width (mm)	920
Height (mm)	1000
Dry weight (Kg)	1200
Silenced	Yes
Super silenced	Yes
Product type	Generator
Voltage regulator	Capacitor
Engine manufacturer	Deutz