



TELWIN SUPERIOR 400 CE VRD MIG PACK 230-400V

Reference: 816041

High power MIG-MAG/FLUX/MMA/TIG multi-process inverter generator suitable for heavy duty use on worksites and industrial environments.

MIG-MAG welding of all types of steels and steel by-products and MMA welding of all types of electrodes up to 6 mm in diameter.

The optional removable wire feeder and connection cables make it possible to increase the field of intervention.

Compactness and easy transport features guarantee high levels of mobility and flexibility of use.

Complete with wirefeeder, MIG-MAG welding accessories, trolley.

Not binding images and technical data.

Technical Sheet

Phase	Single phase / Three phase
Frequency (Hz)	50 / 60
Voltage (V)	230 / 400
Efficiency (%)	86
Protection degree	IP23
No-load voltage (V)	63 / 62
Regulation current (A)	10 - 300 / 10 - 350
Diameter electrodes (mm)	1.6 - 6
Ø steel welding wire (mm)	0.6 - 1.6
Ø inox welding wire (mm)	0.8 - 1.6
Ø aluminium welding wire (mm)	0.8 - 1.6
Ø flux cored welding wire (mm)	1 - 1.6
Ø brazing wire (mm)	0.8 - 1.2
Type of welding	Multiprocess
MIG-MAG welding	MIG-MAG/FLUX
Current max (A)	250 / 330
Length (mm)	950

Width (mm)	450
Height (mm)	1200
Voltage regulator	Inverter
Weight (Kg)	68
