



MARINE GENERATOR KOHLER 16EKOZD SINGLE-PHASE 15KVA 60Hz EPA

Reference: KOHLER 16 EKOZD 60hz

Super-silenced single-phase KOHLER 16EKOZD marine generator 15 KVA AVR

Kohler 16EKOZD Marine generator single phase 15 KVA with 1800 rpm motor EPA certified. The KOHLER 16EKOZD single-phase marine generator is built with a soundproof enclosure that makes it **supersilenced**. The KOHLER 16EKOZD single-phase marine generator is built with a 4-cylinder, 4-cycle Kohler diesel-powered engine, closed cooling system with heat exchanger. The alternator of the single-phase KOHLER 16EKOZD marine generator is brushless with **AVR** voltage regulator and water-cooled.

Features of the KOHLER 16EKOZD marine generator

- Class H insulation
- Multi-voltage adjustability
- Voltage adjustment of 1.0%.
- Radio suppression

Engine features of the KOHLER 16EKOZD marine generator

- Diesel
- Environmental Protection Agency (EPA) certified for compliance with Tier III marine auxiliary standards
- Four cylinders
- Four cycles
- Closed cooling system
- Heat exchanger
- Electric fuel lift pump
- Lifting eyelet
- Low oil pressure shutdown
- High temperature engine shutdown
- Low seawater pressure shutdown
- Vibromount
- Belt guard
- Disposable oil filter
- Oil drain valve
- Disposable fuel filter

TECHNICAL FEATURES KOHLER 16EKOZD

Phase Type: Single-Phase
Maximum Single-Phase Power: 15 KW
Fuel: Diesel
Frequency: 60 Hz

Voltage: 120/240 V
Motor: Kohler
Emissions Regulation: EPA
Engine RPM: 1800 rpm
Length: 1064 mm
Width: 652.5 mm
Height: 711 mm
Dry Weight: 393 Kg

Other marine generators such as the KOHLER 16EKOZD can be found by browsing the entire catalog of [marine generators](#).

Pictures and technical data are not binding.

Technical Sheet

Phase	Single phase
Continuous power single phase (KW)	15
Continuous power single phase (KVA)	15
Fuel	Diesel
Frequency (Hz)	60
Engine	Kohler
Emissions Regulations	EPA
Engine rpm (rpm)	1800
Speed governor	Mechanical
Engine capacity (cm ³)	1900
Number cylinders	3
Cooling	Water
Bore x stroke (mm)	88 x 102
Compression ratio	17 : 1
Motor insulation class	H
Consumption (L/h)	3.51 at 75% of the load
Length (mm)	1064
Width (mm)	652.5
Height (mm)	711
Dry weight (Kg)	393
Silenced	Yes
Super silenced	Yes
Type of combustion	Direct
Voltage regulator	AVR

Engine manufacturer

Kohler