



- ✿ Transportable. Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.
- ✿ Stackable. Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.
- ✿ Accessible. Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.
- ✿ Efficient. Lockable equipment cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel-powered equipment.
- ✿ Environmentally Safe. Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

SPECIFICATIONS*

STANDARD FITTINGS: High accuracy contents gauge; 3" Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return portset; pressure/vacuum vent; breather vent.

OPTIONAL FITTINGS: Complete transfer pump kits; water & particulate filter kits; fuel up to (2) feed & return blocks; fuel hose & quick couplers.

Capacity (Brim-Fill) Litres: 3000	Dimension Height (mm/in): 1315 mm/51.77"
Capacity (Brim-Fill) Imperial Gallons: 660	Weight Empty (lbs/kg): 2234 lbs (1013kg)
Capacity (Brim-Fill) US Gallons: 793	Weight Full (lbs/kg): 8855 lbs (4016kg)
Dimension Length (mm/in): 2298 mm/90.45"	Approvals: UL142, ULC S-601-07, SUN IBC Type 31A,
Dimension Width (mm/in): 1548 mm/60.94"	UN DOT, NFPA, Transport Canada, Vlare, Kiwa